

Chrome metal

Vacuum grade - Low nitrogen

Vacuum grade chrome metal is primarily used for production of superalloys, where low gas content is critical.



01 Standard Specifications

	Al	Fe	Si	O	N	C	S	P	Cr
Max (ppm)	1000*	2000	1000	1300	150*	150	80	20	Min (%) 99,6%
Typical (ppm)	500	1200	500	1000	100	80	60	10	

*Other Chrome metal vacuum grades are available, including but not limited to :

VG LN (Vacuum Grade Low Nitrogen) : N 50 ppm max

VG ULN (Vacuum Grade Ultra Low Nitrogen) : N 25 ppm max

VG LAI (Vacuum Grade Low Aluminium) : Al 100 ppm max

02 Size

Lumps 2" by down (0-50 mm), or according to specifications

03 Packing

Steel drums 500 lb / 250 kg

Customs tariff 81122190
REACH registration no. 01-2119485652-31-0039



CONTACT

info@dcx-chrome.com

Head office and plant location
DCX Chrome SAS
- Delachaux Group
68, rue Jean Jaurès
59770 Marly, France
Tel +33 3 27 20 07 77

USA - Delachaux Metal Inc.
26 Interstate Drive - P.O. Box 69
Napoleon, Ohio 43545 - USA
Phone 631-373-0212

DCX CHROME

⊕ GROUPE DELACHAUX